

UBB SYSTEM COMPATIBILITY CHART

ENCOMPASSING ALL BOTTOM BRACKET STANDARDS

- ▣ ROTOR's "UBB" is a super-standard that encompasses all BB standards. It allows installation of almost any 30 or 24 mm axle crank from ROTOR on the bike you have, regardless of its BB type. It works with everything!
- ▣ The charts below help you identify the BB type of a bike you are installing ROTOR cranks on. It then tells you which BB and crankset combinations will work.



THREADED BB		NON THREADED BB							
		D = 37 mm BB90	D = 41 mm	D = 42 mm		D = 46 mm			
		W = 68 mm BSA	W = 70 mm ITA	W = 86 mm BB86	W = 68 mm BB30	W = 79 mm BBRight California	W = 68 mm PressFit30	W = 79 mm BBRight PF	W = 86 mm BB386EVO
24 mm SPINDLE	BB1 BSA SABB BSA TRACK BSA 3D <small>(All Shimano compatible)</small>	BB1 ITA SABB ITA TRACK BSA 3D <small>(All Shimano compatible)</small>	3D <small>(All Shimano compatible)</small>	Press Fit 4124 3D <small>(All Shimano compatible)</small>	BB30 to 24 Road 3D <small>(All Shimano compatible)</small>		Press Fit 4624 Road 3D <small>(All Shimano compatible)</small>	BBRight 4624 3D <small>(All Shimano compatible)</small>	
	BSA30 3D+ 3DF FLOW POWER	ITA30 3D+ 3DF FLOW POWER		Press Fit 4130 3D+ 3DF FLOW POWER	BB30 BEARING KIT 3D+ 3DF FLOW POWER	BB30 BEARING KIT 3D+ 3DF FLOW POWER	Press Fit 4630 3D+ 3DF FLOW POWER	Press Fit 4630 3D+ 3DF FLOW POWER	Press Fit 4630 3D+ 3DF FLOW POWER

ROAD / TRI CARRETERA / TRIATLÓN